CUTTING OIL

DRILLING AND CUTTING LUBRICANT
GT-CUT10 art. 84010



Innovative Lubricant high-quality product, it gives protective action for tools and equipment in the mechanical industry. GT-CUT10 is developed for specific professional applications in hard metal cutting and machining operations.
Oil with a paraffin mineral base enriched with special EP anti-weld additives.
Ideal for use in difficult threading operations with particularly hard, alloy steel.
Suited for use in the hydraulic sector.

Technical Characteristics

Color	light brown
Odour	characteristic of solvent
Relative Density at 20°C	0,75 ÷ 0,80 g/ml
Flash Point	< 0° C
Pressure at 20°C	4/6 bar

Packaging

Tin-Plate Aerosol cans 15 bar, 400 ml

Labelling



IRRITANT



EXTREMELY FLAMMABLE



DANGEROUS FOR THE ENVIRONMENT

EN: Vapours may cause drowsiness and dizziness. Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment Irritating to skin. Extremely flammable.

This information, although believed to be reliable, must be regarded as indicative. Their use does not imply any our responsibility , including the violation of any patents or licenses. Is a user's responsibility to check advance the suitability of the product for the specific use.