

TECHNICAL DATASHEET
GT-Z06 Bright zinc galvanising spray

EN
rev. 07/2014
p. 1/2

BRIGHT ZINC

Protective, anti-rust and corrosion

GT-Z06 art. 84006

Cold Zinc spray with high molecular weight, it chemically solidifies producing a long lasting metal coating. It's ideal for retouches and finishing joints, welds and repairs of galvanized parts, when a light gray finish is required. Suitable for railings and gates, metal, steel, automotive, hydraulics and accessories, gutters, welding works, repair of tanks and cisterns, metallic carpentry, construction, garages, do-it-yourself.

Excellent resistance to corrosion, to rust and to weathering on all ferrous materials.

Forms a high elasticity protection layer that resists cracking and fading. It dries quickly and does not drip.

It can be left as a final protection or sanded and/or painted over.



Technical characteristics

Colour	aluminium/light gray
Odour	characteristic of solvent
Relative density at 20°C	0,75 ÷ 0,80 g/ml
Temperature resistance	400 °C
Dry residue of zinc	10 %
Drying times	
Out dust	10 min.
Dry to touch	20 min.
Dry in depth	24 h
Layer thickness	15 ÷ 20 µm
Yield	2 ÷ 2,5 m ² per cylinder
Flash point	< 0°C
Pressure at 20°C	4/6 bar

Packaging

Tinplate aerosol cans 15 bar, 400 ml

TECHNICAL DATASHEET
GT-Z06 Bright zinc galvanising spray

EN
rev. 07/2014
p. 2/2

Labelling



EXTREMELY
FLAMMABLE



DANGEROUS FOR
ENVIRONMENT

R-phrases

Extremely flammable

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment

Vapours may cause drowsiness and dizziness

This information, although believed to be reliable, must be regarded as indicative. Its use does not imply any responsibility from our part. It's user's responsibility to check in advance the suitability of the product for the specific use.